

1. General Description

This Document contains the log data of a read out logfile. It shows what happened with the specified vbar unit during the latest time

Version of PC Software	5.3.2 07.07.2012
Date	Wed Jun 25 22:16:27 MSK 2014
Serial	1520001315
Prod Date	7.9.2012 9:22
Firmware	5.3
Patchlevel	4

2. Chronological List of Events

⚠	0:05	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	0:05	Governor is at Low Throttle Limit	There is a defined low limit, that the Governor will not fall below. If this Limit is reached, this Info Message is issued. The Message is issued once for each touch of the limit. If the limit is touched, it means that your headspeed will be higher than programmed.
✖	0:15	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
⚠	0:24	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
⚠	0:27	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
⚠	0:34	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	0:44	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:54	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:04	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:14	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:24	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
⚠	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered by manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
⚠	0:00	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
⚠	0:05	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:45	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	0:51	Governor ON	Governor switched to mode ON
⚠	0:57	Governor is at Low Throttle Limit	There is a defined low limit, that the Governor will not fall below. If this Limit is reached, this Info Message is issued. The Message is issued once for each touch of the limit. If the limit is touched, it means that your headspeed will be higher than programmed.
✔	1:07	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	1:14	Governor ON	Governor switched to mode ON
⚠	1:14	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
⚠	1:15	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
⚠	1:16	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds

▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
▶	0:05	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:45	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:07	Governor ON	Governor switched to mode ON
▶	1:13	Governor is at Low Throttle Limit	There is a defined low limit, that the Governor will not fall below. lth this Limit is reached, this Info Message is issued. The Message is issued once for each touch of the limit. If the limit is touched, it means that your headspeed will be higher than programmed.
▶	1:16	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and chis is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeditly very often, check the heli for vibration sources.
⚠	1:26	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
⚠	1:36	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additinally slow drifts that happen may be caused by vibrations.
✖	1:45	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
✖	1:47	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleed on ground, or on very hard landings or very extreme Vibrations.
✖	1:47	Elevator Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleed on ground, or on very hard landings or very extreme Vibrations.
▶	1:47	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
▶	1:51	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	1:52	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	1:53	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	1:54	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	1:55	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✖	1:55	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	1:58	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	2:01	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
▶	2:02	Antenna Switched	The Signal from one of the sattelites was missing. The Main reciver is switched over to the other connector. In Case of a single reciver connected, one frame was lost.
✔	2:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.

✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered by manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Stop	Governor switched to mode Stop, Servo to minimum
▶	0:05	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:45	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.